



Boron Nitride Grade M & M26

Boron Nitride is an advanced synthetic ceramic material available in powder, solid, liquid and aerosol spray forms. Its unique properties - from high heat capacity and outstanding thermal conductivity to easy machinability and superior dielectric strength - make boron nitride a truly outstanding material.

Solid Boron Nitride Grade M is a truly hydrophobic advanced ceramic. Composed of boron nitride and silica, it is completely resistant to moisture and has a MIL-I-10A grade of L542, a test requiring immersion in water for 48 hours prior to testing at elevated frequencies. Grade M is suitable for the most severe electrical applications. It is an excellent refractory material at temperatures up to 1400°C, and is unparalleled in resistance to thermal shock.

Applications

- High temperature electrical insulators and vacuum furnace supports which require electrical resistivity, high temperature strength, thermal shock resistance and low chemical resistivity
- Crucibles and containers for high purity molten metals
- Tools and refractories for glass forming which provide non-wetting, non-B₂O₃ containing contacts
- Radar components and antenna windows which require exacting electrical and thermal properties

Typical Properties		
Typical Chemical Analysis	Grade M	Grade M26
Boron ¹	18-20.25%	26.5-28.7%
Nitrogen ¹	22.5-25.5%	32.8-35%
Oxygen ¹	-	-
Calcium ¹	.01% ³	.01% ³
Silica (SiO ₂) ¹	60%	40% ¹
Other Inorganic ¹	.02%	.05%
Trace Metals	.05%	.05%
TOTAL	100%	100%
B ₂ O ₃ *	.2%	.2%

*B₂O₃ is given for clarification and is not part of the elemental analysis
¹ Wet Chemistry - ² LECD Oxygen - ³ Optical Emission Spectroscopy

Typical Physical Properties				
Typical Physical Properties	Grade M		Grade M26	
Percent BN:	40		60	
Percent SiO ₂ :	60		40	
	Parallel	Perpendicular	Parallel	Perpendicular
Volume Resistivity (ohm-cm) @RT:	1.7x10 ¹⁵	5.1x10 ¹⁵	6.4x10 ¹⁴	2.9x10 ¹⁵
@150°C:	2.4x10 ¹³	3.3x10 ¹³	2.4x10 ¹³	8.5x10 ¹³
Dielectric Constant (@ 1MHz) @RT:	4.21	3.87	4.48	3.89
microwave frequency: @ RT, 8.8 GHz:	3.86	4.08	3.89	4.28
Dielectric Strength: volts/mil & (volts/mm)				
Sample thickness: 10 mil	1670 (65748)		1690 (66535)	
Tested up to 25kV) 25 mil	>1000 (>39370)		>1000 (>39370)	
Dissipation Factor (Loss tangent)				
@RT @ 1MHz	.0016	.0035	.0017	.0061
@150°C @ 1MHz	.0017	.0055	.0094	.0062
@RT @ 8.8GHz	.0011	.0005	.0039	.0006
Loss Factor				
@RT @ 1MHz	.0067	.0140	.0076	.0230
@150°C @ 1MHz	.0077	.0230	.0440	.0250
@RT @ 8.8GHz	.0042	.0020	.0150	.0260
Surface Resistivity (ohms/) @ RT	8.5 x 10 ¹⁶		4.2 x 10 ¹⁶	
@ 150°C	1.4 x 10 ¹⁵		1.5 x 10 ¹⁵	

The values presented are mean and typical of those resulted from test samples. They are provided as an indication only to serve as guidance in the design of ceramic components and are not guaranteed in any way. The actual values can vary according to the shape and size of the envisaged component.



PRECISION CERAMICS

86 Lower Tower Street, Birmingham B19 3PA, England
 Tel: +44 (0) 121 687 5858 Fax: +44 (0) 121 687 5857
 Email: info@precision-ceramics.co.uk
www.precision-ceramics.co.uk